

FATHOM LEVER DRAG 2-SPEED

• Full Metal Body and sideplates • Forged and machined aluminum spool • Stainless steel main and pinion gear			• Dura-Drag™ washers virtually eliminate hesitation, even under extreme drag settings • Quick-Shift™ 2-speed system			• 5 shielded stainless steel ball bearings • Double-dog ratchet anti-reverse • Line Capacity Rings				
Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearings	Max Drag @ Strike	Max Drag @ Full	Max Drag @ Sunset	Gear Ratio High/Low	Line Retrieve (in)High/Low	Weight (oz)
FTH15LD2	1292931	355/12 • 305/15 • 200/20	550/20 • 415/30 • 290/50	5	13 lbs	16 lbs	20 lbs	6.1:1 / 2.8:1	31/14	15.6
FTH25NLD2	1292932	330/20 • 305/25 • 245/30	680/30 • 475/50 • 395/65	5	23 lbs	28 lbs	33 lbs	5.5:1 / 2.7:1	38/19	19.6
FTH30LD2	1292933	440/20 • 330/30 • 255/40	635/50 • 525/65 • 455/80	5	23 lbs	28 lbs	33 lbs	5.5:1 / 2.7:1	38/19	20.0
FTH40NLD2	1292934	410/30 • 315/40 • 235/50	785/50 • 655/65 • 565/80	5	23 lbs	28 lbs	40 lbs	5.0:1 / 2.5:1	42/21	25.7
FTH60LD2	1292935	480/40 • 355/50 • 315/60	995/65 • 860/80 • 735/100	5	23 lbs	28 lbs	40 lbs	5.0:1 / 2.5:1	42/21	27.3

• TOPSHOT capacities are located in the Master Capacity Chart.



The stainless steel gear train in our Fathom Lever Drag reels doesn't get much tougher. Machined from stainless steel and drilled out for weight reduction, these gears offer the perfect combination of strength and speed.





Our **Dura-Drag** material contains a special Phenolic bonding agent that prevents premature breakdown of the carbon fiber material while providing a barrier to water. We then pretreat each drag washer with a special compound developed by PENN engineers.....say good by to jerky drags and lost fish.

FATHOM LEVER DRAG

• Full Metal Body and sideplates • Forged and machined aluminum spool • Stainless steel main and pinion gear			• Dura-Drag™ washers virtually eliminate hesitation, even under extreme drag settings			• Line Capacity Rings • 5 shielded stainless steel ball bearings				
Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearings	Max Drag @ Strike	Max Drag @ Full	Max Drag @ Sunset	Gear Ratio	Line Retrieve (in)	Weight (oz)
FTH15LD	1338210	355/12 • 305/15 • 200/20	550/20 • 415/30 • 290/50	5	13 lbs	16 lbs	20 lbs	5.3:1	27	15.1
FTH25NLD	1338211	330/20 • 305/25 • 245/30	680/30 • 475/50 • 395/65	5	23 lbs	28 lbs	33 lbs	5.3:1	36	19.4
FTH30LD	1338212	440/20 • 330/30 • 255/40	635/50 • 525/65 • 455/80	5	23 lbs	28 lbs	33 lbs	5.3:1	36	19.8
FTH40NLD	1338213	410/30 • 315/40 • 235/50	785/50 • 655/65 • 565/80	5	23 lbs	28 lbs	40 lbs	4.8:1	40	24.7
FTH40NLDHS	1338214	410/30 • 315/40 • 235/50	785/50 • 655/65 • 565/80	5	23 lbs	28 lbs	40 lbs	7.1:1	60	24.7

• TOPSHOT capacities are located in the Master Capacity Chart.



The stainless steel gear train in our Fathom Lever Drag reels doesn't get much tougher. Machined from stainless steel and drilled out for weight reduction, these gears offer the perfect combination of strength and speed.





Our **Dura-Drag** material contains a special Phenolic bonding agent that prevents premature breakdown of the carbon fiber material while providing a barrier to water. We then pretreat each drag washer with a special compound developed by PENN engineers.....say good by to jerky drags and lost fish.

AVAILABLE IN HIGH SPEED MODEL 40NLDHS